

Galvanized Utility Cables

- 7 x 19 Galvanized Utility Cable is used for lift lines, guide wires, and other applications requiring an economical wire rope with good strength and flexibility
- Manufactured to Federal Specification RRW-410E
- Test certificates are available at extra cost
- Sold in 2500' (762 m) rolls
- Other types of wire rope are available for special applications
- Three-year warranty against defects in materials or workmanship is provided on all J.R. Clancy equipment, additional warranty information is available at jrclancy.com



Galvanized Utility Cable
020-125

Order Information

Number	Description	RWL	Weight
2,500' (762 m) Rolls, wt. per foot (meter)			
020-125	1/8" (3 mm) Galvanized Utility Cable	250 lb (113 kg)	0.03 lb (0.01 kg)
020-187	3/16" (5 mm) Galvanized Utility Cable	537 lb (243 kg)	0.07 lb (0.03 kg)
020-250	1/4" (6 mm) Galvanized Utility Cable	875 lb (397 kg)	0.11 lb (0.05 kg)
020-312	5/16" (8 mm) Galvanized Utility Cable	1225 lb (556 kg)	0.18 lb (0.08 kg)
020-375	3/8" (10 mm) Galvanized Utility Cable	1800 lb (816 kg)	0.25 lb (0.11 kg)
500' (152.4 m) Convenience Rolls, wt. per roll			
020-125-5	1/8" (3 mm) Galvanized Utility Cable	250 lb (113 kg)	15 lb (6.8 kg)
020-375-5	3/8" (10 mm) Galvanized Utility Cable	1800 lb (816 kg)	90 lb (40.8 kg)
RWL is based on an 8:1 safety factor.			

