Technical Sheet

Transform[®] Motorized Acoustical Banner



Available fabric options: - Encore Velour, double layer 22 oz (0.6 kg) - Wool Serge, double layer 30 oz (0.85 kg) See table below for banner fabric options **Fully Retracted** Tubular motor driven system Partially Deployed **Fully Deployed** for use in an operator controlled to 30' (9144 mm) or preset environment Designed for performance spaces. including performance halls, theaters, and auditoriums All fabrics are IFR rated Each banner option includes adjustable spacing away from the wall and between the layers of fabric - From wall to rear fabric: 4" to 6" (102 to 152 mm) - Between fabric layers: 3" to 5" (76 to 127 mm) Each banner includes a standard "guick change" provision to allow fabric to be removed for maintenance Banner retracts into cove to hide from view when not in use Banner includes laminated wood closures Enclosure width will vary to match fabric width ٠ For exposed installations, end caps are included in a variety of finishes Fast and quiet deployment of up to 45' (13716 mm) per minute A minimum 2" (51 mm) of spacing between banner enclosures is recommended Wall and ceiling mount kits are available for fast and easy installation • Banner system will integrate with J.R. Clancy's systems or simple push button controls • Requires a standard 120V/60 Hz circuit, 2.1A maximum per banner (worldwide voltages available) Each banner is shipped assembled and tested for proper operation before shipment Patents pending ٠ Three-year warranty Lower and Raise the Adjustable Fabric Banner **Transform Banner Fabric Options** Horizontal Minimum Maximum Maximum Fabric Type Seams¹ Width Width Height 32" (0.81 m) 58" (1.47 m) 360" (9.14 m) No Wool Serge Yes 59" (1.50 m) 116" (2.94 m) 180" (4.57 m) No 32" (0.81 m) 64" (1.62 m) 360" (9.14 m) Encore Velour Yes 65" (1.65 m) 116" (2.94 m) 180" (4.57 m) ¹ Wider banner fabric requires front-facing horizontal seams

