

# ENCORE™

22 oz. 64" / 15 oz. 62" WIDE · 100% POLYESTER

INHERENTLY FLAME RETARDANT



ENCORE™ 22 oz. / 64" WIDE CABERNET



ENCORE™ 15 oz. / 62" WIDE BLACK



WHITE




BEIGE



CORONA



IRIS



PEWTER



SLATE



ICE BLUE



BERMUDA



ROYAL BLUE



PROVINCIAL



CYPRESS



CRIMSON



PLUM



ESPRESSO

All colors subject to dye lot variation.



# ROSE BRAND®

Theatrical Fabrics, Fabrications & Supplies

800.223.1624 800.360.5056 RoseBrand.com V-3

# ENCORE™

## FABRIC SPECIFICATIONS

QUALITY	22 oz. VELOUR	15 oz. VELOUR
<b>COMPOSITION:</b>	<b>100% polyester</b>	<b>100% polyester</b>
<b>WIDTH:</b>	64" (162 cm)	62" (157 cm)
<b>WEIGHT:</b>	22 oz./yd. (625 g/m)	15 oz./yd. (425 g/m)
<b>FINISH:</b>	Inherently Flame Retardant	Inherently Flame Retardant
<b>FLAME TESTING:</b>	UFAC Class 1 NFPA 701 - TM #1 (2010 ed.) Calif. Title 19, Reg.#F-521.01 NYC FD Reg #5135 CAN/UL S-109 German DIN 4102 B1 IMOa.471(XII)-A.563 ASTM E-84 Class A	UFAC Class 1 NFPA 701 - TM #1 (2010 ed.) Calif. Title 19, Reg.#F-521.01 NYC FD Reg #5135 CAN/UL S-109 ASTM E-84 Class A German DIN 4102 B1
<b>TEAR STRENGTH:</b>		
Trap (ASTM D5587)	Warp - 32 lbs (142 N) Filling - 52 lbs (231 N)	Warp - 16 lbs (71 N) Filling - 13 lbs (58 N)
Tongue (ASTM D2261)	Warp - 5 lbs (23 N) Filling - 12 lbs (53 N)	Warp - 4 lbs (16 N) Filling - 12 lbs (53 N)
<b>TENSILE STRENGTH:</b>		
Grab (ASTM D5034)	Warp - 60 lbs (266 N) Filling - 147 lbs (653 N)	Warp - 64 lbs (284 N) Filling - 66 lbs (293 N)
Strip (ASTM D5055)	Warp - 23 lbs (102 N) Filling - 100 lbs (444 N)	Warp - 36 lbs (160 N) Filling - 40 lbs (178 N)
<b>ABRASION:</b>		
Wyzenbeek (ASTM D3597)	Exceeds 15,000	Exceeds 15,000
Martindale (ASTM D4966)	Double Rubs Exceeds 35,000 Cycles	Double Rubs Exceeds 35,000 Cycles
<b>LIGHT FASTNESS:</b>	40 to 80 hrs (varies by color)	40 to 80 hrs (varies by color)
(ASTM D3597, Xenon)		
<b>CROCKING:</b>	Wet - 3 to 5 (varies by color) Dry - 3 to 5 (varies by color)	Wet - 3 to 5 (varies by color) Dry - 3 to 5 (varies by color)
(AATCC 107)		

### CARE AND CLEANING INSTRUCTIONS

- 1. Regular Care -** Vacuum to remove ordinary lint and dust.
- 2. Spot Cleaning -** Most spots and stains can be removed with a damp sponge, mild cleaning fluids, or dry cleaning powders. None of these methods should cause spotting.
- 3. General Cleaning -** Professional dry cleaning service is recommended. Water washing (120-160°F) using mild detergent and non-chlorine bleach is an option. Tumble dry medium heat. Supplementary flame testing is recommended after repeated dry cleaning or washings to ensure that the curtain meets local fire codes.