

# A-Guide™ System

- Heavy duty aluminum guide system for counterweight arbors
- 2" x 3-1/2" x 3/16" (51 mm x 89 mm x 5 mm) guide
- Significantly less time to install than steel T-Bar
- 6" (152 mm) and 8" (203 mm) centers are standard, other centers are available
- A-Guide systems supplied complete with required A-Guide, wall battens, stop battens, splices, adjustable wall knees, bolts, nuts, and washers
- Adjustable wall knees allow simple, on site adjustment to meet field conditions
- Vertical A's are connected to wall battens with self-aligning clamps, for fast installation  
Pre-punched horizontal wall battens and stop battens are pre-punched  
1-3/4" x 1-3/4" x 3/16" (45 mm x 45 mm x 5 mm) steel angle, with holes on 2" (51 mm) centers  
These allow simple adjustment of guide location to accommodate field conditions
- Optional 2" x 2" (51 mm x 51 mm) hardwood or hardwood with neoprene bumpers are available for stop battens
- Three-year warranty against defects in materials or workmanship is provided on all J.R. Clancy equipment, additional warranty information is available at jrclancy.com



**A-Guide System**  
**012-1751**  
**US Patent 6,537,155**

## Ordering Information

Guide systems are ordered in linear feet of guide required (number of runs of A x height of guide).

Number	Description	Weight
012-1751	A-Guide System, black anodized finish	4 lb/ft (5.9 kg/m)
112-1H	2" x 2" (51 mm x 51 mm) Hardwood stop batten	3 lb/ft (4.46 kg/m)
112-1N	2" x 2" (51 mm x 51 mm) Hardwood stop batten w/ 1/4" (6 mm) Neoprene	4 lb/ft (5.9 kg/m)

