

# Fire Curtains

- Provides a fire-rated barrier between the stage and auditorium, as required by the International Building Code (IBC) and other building codes
- Brail or Straight Lift styles, to suit your stage architecture
- Manual or Motorized – all curtains close automatically when activated, non-emergency operations can be motorized for convenience or code compliance
- Zetex<sup>®</sup> Plus 1210ZP curtains (40 oz/sq yd [1.36 kg/m<sup>2</sup>]) are Listed by the State of California Fire Marshall (1670-1164:0101), and by the NYC Department of Buildings Materials and Equipment Acceptance Division (MEA 212-08-M); listings are for curtains with or without wire insertion
- Zetex<sup>®</sup> Plus 1210ZP curtains have a 30 minute rating and meet or exceed most fire code requirements
- Fabric is available in natural (tan) or black
- Framed-type curtains also available
- Fire curtain systems meet ANSI E1.22 "Entertainment Technology Fire Safety Curtain Systems" or NFPA 80 "Standard for Fire Doors and Other Opening Protectives"
- Three-year warranty against defects in materials or workmanship is provided on all J.R. Clancy equipment, additional warranty information is available at jrclancy.com

## Order Information

Number	Description
017-1201	<b>Zetex Fire Curtain, Straight Lift</b>
017-1201B	<b>Zetex Fire Curtain, Straight Lift, Black</b>
017-1201BW	<b>Zetex Fire Curtain, Straight Lift, Black, Wire Inserted</b>
017-1201W	<b>Zetex Fire Curtain, Straight Lift, Wire Inserted</b>
017-1203	<b>Zetex Fire Curtain, Brail</b>
017-1203B	<b>Zetex Fire Curtain, Brail, Black</b>
Please provide section and elevation drawings of the proscenium wall area when requesting a quotation.	



**Straight Lift Fire Curtain**

