


FrontLoader® Front Loading Arbor

The FrontLoader® Front Loading Arbor eliminates rods and spreader plates of the conventional rod arbor. Bending and climbing into the arbor well to load bricks is no longer necessary as bricks can now be safely stacked from the loading


- The arbor is comprised of a series of sloped shelves within individually accessible compartments at 2' (610 mm) increments
- Each arbor compartment is designed to accommodate ANSI E1.4.1 compliant counterweight bricks 13-3/4" (349 mm) deep.
 - Arbor models for 6" (152 mm) wide bricks with a minimum guide spacing of 8" (203 mm) center to center and models for 4" (102 mm) wide bricks with a minimum guide spacing of 6" center to center available.
- Arbor height options of 6' (1829 mm) tall, 8' tall (2438 mm), or 10' (3048 mm) tall
- Arbor shall be available as either single purchase operation or double purchase operation
- Compartment latching mechanism shall be a two stage rotary latch system designed to comply with the strength requirements of SAE J839 and FMVSS 206.
 - Further, the pivot axial load meets or exceeds 120 lb-in (13.55 N-m) torque.
- · Arbor housing is constructed of formed 12-gauge steel
- Arbor gates are constructed of resistance welded bar in a grid (mesh) configuration
- Each 2' (610 mm) tall (nominal) arbor gate is attached to the arbor with two hinges rated for a minimum of 400 lb (181 kg) hanging static load each
- Single Purchase Front Loading Arbors ship with a 3/4" (19 mm) round rope thimble (023-750RR) attached for easy hand line installation

Order Information

Number	Height	Width	Style	Arbor Weight	Arbor Capacity
007-FL06-6	6'	6" C-C	Single	92 lb	873 lb
	(1829 mm)	(4" wide counterweight)	Purchase	(42 kg)	(396 kg)
007-FL08-6	8'	6" C-C	Single	112 lb	1164 lb
	(2438 mm)	(4" wide counterweight)	Purchase	(51 kg)	(528 kg)
007-FL10-6	10'	6" C-C	Single	136 lb	1455 lb
	(3048 mm)	(4" wide counterweight)	Purchase	(62 kg)	(660 kg)
007-FL06-8	6'	8" C-C	Single	105 lb	1284 lb
	(1829 mm)	(6" wide counterweight)	Purchase	(48 kg)	(582 kg)
007-FL08-8	8'	8" C-C	Single	132 lb	1712 lb
	(2438 mm)	(6" wide counterweight)	Purchase	(60 kg)	(777 kg)
007-FL10-8	10'	8" C-C	Single	158 lb	2140 lb
	(3048 mm)	(6" wide counterweight)	Purchase	(72 kg)	(971 kg)
008-FL06-6	6'	6" C-C	Double	120 lb	873 lb
	(1829 mm)	(4" wide counterweight)	Purchase	(54 kg)	(396 kg)
008-FL08-6	8'	6" C-C	Double	140 lb	1164 lb
	(2438 mm)	(4" wide counterweight)	Purchase	(64 kg)	(528 kg)
008-FL10-6	10'	6" C-C	Double	164 lb	1455 lb
	(3048 mm)	(4" wide counterweight)	Purchase	(74 kg)	(660 kg)
008-FL06-8	6'	8" C-C	Double	136 lb	1284 lb
	(1829 mm)	(6" wide counterweight)	Purchase	(62 kg)	(582 kg)
008-FL08-8	8'	8" C-C	Double	163 lb	1712 lb
	(2438 mm)	(6" wide counterweight)	Purchase	(74 kg)	(777 kg)
008-FL10-8	10'	8" C-C	Double	189 lb	2140 lb
	(3048 mm)	(6" wide counterweight)	Purchase	(86 kg)	(971 kg)



FrontLoader Single Purchase 007-FL06-8



Double Purchase 008-FL10-8







Owatonna Office: Phone 800.4WENGER (493-6437) Worldwide +1.507.455.4100 | Parts & Service 800.887.7145 | wengercorp.com

555 Park Drive, PO Box 448 | Owatonna | MN 55060-0448

Phone 800.836.1885 Worldwide +1.315.451.3440 | jrclancy.com | 7041 Interstate Island Road | Syracuse | NY 13209-9713 Syracuse Office: