

FrontLoader® Front Loading Arbor

The FrontLoader Front Loading Arbor eliminates rods and spreader plates of the conventional rod arbor. Bending and climbing into the arbor well to load bricks is no longer necessary as bricks can now be safely stacked from the loading gallery.

- The arbor is comprised of a series of sloped shelves within individually accessible compartments at 2' (610 mm) increments
- Each arbor compartment is designed to accommodate ANSI E1.4.1 compliant counterweight bricks 13-3/4" (349 mm) deep; Arbor models for 6" (152 mm) wide bricks with a minimum guide spacing of 8" (203 mm) center to center and models for 4" (102 mm) wide bricks with a minimum guide spacing of 6" center to center available
- Arbor height options of 6' (1829 mm) tall, 8' tall (2438 mm), or 10' (3048 mm) tall
- Arbor shall be available as either single purchase operation or double purchase operation
- Compartment latching mechanism shall be a two stage rotary latch system designed to comply with the strength requirements of SAE J839 and FMVSS 206; Further, the pivot axial load meets or exceeds 120 lb-in (13.55 N-m) torque.
- Arbor housing is constructed of formed 12-gauge steel
- Arbor gates are constructed of resistance welded bar in a grid (mesh) configuration
- Each 2' (610 mm) tall (nominal) arbor gate is attached to the arbor with two hinges rated for a minimum of 400 lb (181 kg) hanging static load each
- Single Purchase Front Loading Arbors ship with a 3/4" (19 mm) round rope thimble (023-750RR) attached for easy hand line installation
- Three-year warranty against defects in materials or workmanship is provided on all J.R. Clancy equipment, additional warranty information is available at jrclancy.com

Order Information

Number	Height	Width	Style	Arbor Weight	Arbor Capacity
007-FL06-6	6' (1829 mm)	6" C-C (4" wide counterweight)	Single Purchase	92 lb (42 kg)	873 lb (396 kg)
007-FL08-6	8' (2438 mm)	6" C-C (4" wide counterweight)	Single Purchase	112 lb (51 kg)	1164 lb (528 kg)
007-FL10-6	10' (3048 mm)	6" C-C (4" wide counterweight)	Single Purchase	136 lb (62 kg)	1455 lb (660 kg)
007-FL06-8	6' (1829 mm)	8" C-C (6" wide counterweight)	Single Purchase	105 lb (48 kg)	1284 lb (582 kg)
007-FL08-8	8' (2438 mm)	8" C-C (6" wide counterweight)	Single Purchase	132 lb (60 kg)	1712 lb (777 kg)
007-FL10-8	10' (3048 mm)	8" C-C (6" wide counterweight)	Single Purchase	158 lb (72 kg)	2140 lb (971 kg)
008-FL06-6	6' (1829 mm)	6" C-C (4" wide counterweight)	Double Purchase	120 lb (54 kg)	873 lb (396 kg)
008-FL08-6	8' (2438 mm)	6" C-C (4" wide counterweight)	Double Purchase	140 lb (64 kg)	1164 lb (528 kg)
008-FL10-6	10' (3048 mm)	6" C-C (4" wide counterweight)	Double Purchase	164 lb (74 kg)	1455 lb (660 kg)
008-FL06-8	6' (1829 mm)	8" C-C (6" wide counterweight)	Double Purchase	136 lb (62 kg)	1284 lb (582 kg)
008-FL08-8	8' (2438 mm)	8" C-C (6" wide counterweight)	Double Purchase	163 lb (74 kg)	1712 lb (777 kg)
008-FL10-8	10' (3048 mm)	8" C-C (6" wide counterweight)	Double Purchase	189 lb (86 kg)	2140 lb (971 kg)

