

# Galvanized Utility Cables

- 7 x 19 Galvanized Utility Cable is used for lift lines, guide wires, and other applications requiring an economical wire rope with good strength and flexibility.
- Manufactured to Federal Specification RRW-410E.
- Test certificates are available at extra cost.
- Sold in 2500' (762 m) rolls.
- Other types of wire rope are available for special applications.



Galvanized Utility Cable  
020-125

## Order Information

Number	Description	RWL	Weight
<b>2,500' (762 m) Rolls, wt. per foot (meter)</b>			
020-125	1/8" (3 mm) Galvanized Utility Cable	250 lbs. (113 kg)	0.03 lb. (0.01 kg)
020-187	3/16" (5 mm) Galvanized Utility Cable	537 lbs. (243 kg)	0.07 lb. (0.03 kg)
020-250	1/4" (6 mm) Galvanized Utility Cable	875 lbs. (397 kg)	0.11 lb. (0.05 kg)
020-312	5/16" (8 mm) Galvanized Utility Cable	1225 lbs. (556 kg)	0.18 lb. (0.08 kg)
020-375	3/8" (10 mm) Galvanized Utility Cable	1800 lbs. (816 kg)	0.25 lb. (0.11 kg)
<b>500' (152.4 m) Convenience Rolls, wt. per roll</b>			
020-125-5	1/8" (3 mm) Galvanized Utility Cable	250 lbs. (113 kg)	15 lbs. (6.8 kg)
020-375-5	3/8" (10 mm) Galvanized Utility Cable	1800 lbs. (816 kg)	90 lbs. (40.8 kg)
RWL is based on an 8:1 safety factor.			

