

Multiline II™ Synthetic Rope

- A popular replacement for manila and other ropes used backstage.
- Conventional, three-strand construction for a familiar feel and strong grip.
- Minimal stretch for easy use.
- Length does not change with temperature or humidity, so floor block readjustment is not necessary.
- Breaking strength is more than twice that of manila rope.
- Sold in 600' (183 m) and 1200' (366 m) rolls.
- Other sizes and colors available on special order.
- For 3/4" (19 mm) rope use SureGrip®.



Multiline II Synthetic Rope

Order Information

Number	Description	RWL	Weight
028-625MW6	5/8" (16 mm) Diameter Multiline II 600' Roll (183 m)	823 lbs. (373 kg)	0.10 lb./ft. (0.13 kg/m)
028-625MW12	5/8" (16 mm) Diameter Multiline II 1200' Roll (366 m)	823 lbs. (373 kg)	0.10 lb./ft. (0.13 kg/m)
028-625MB6	5/8" (16 mm) Diameter Multiline II, Black 600' Roll (183 m)	823 lbs. (373 kg)	0.10 lb./ft. (0.13 kg/m)
028-625MB12	5/8" (16 mm) Diameter Multiline II, Black 1200' Roll (366 m)	823 lbs. (373 kg)	0.10 lb./ft. (0.13 kg/m)
028-875MW6	7/8" (22 mm) Diameter Multiline II 600' Roll (183 m)	1550 lbs. (703 kg)	0.18 lb./ft. (0.27 kg/m)
028-875MW12	7/8" (22 mm) Diameter Multiline II 1200' Roll (366 m)	1550 lbs. (703 kg)	0.18 lb./ft. (0.27 kg/m)
028-1000MW6	1" (25 mm) Diameter Multiline II 600' Roll (183 m)	1870 lbs. (848 kg)	0.22 lb./ft. (0.33 kg/m)
028-1000MW12	1" (25 mm) Diameter Multiline II 1200' Roll (366 m)	1870 lbs. (848 kg)	0.22 lb./ft. (0.33 kg/m)

RWL is based on manufacturer's 10:1 safety factor.



© 2017 Wenger Corporation
USA/2017-12/W

