

Nicopress® Fittings

- Copper oval sleeves are used with a thimble for cable terminations.
- Oval sleeves used with galvanized utility cable have an efficiency rating of 100% of the catalog breaking strength of the galvanized utility cable.
- Copper stop sleeves are used on cable ends inside drums, etc.
The efficiency of these connections must be determined by testing.
- Nicopress sleeves must be installed using the proper Nicopress hand or hydraulic tool.
- Crimps must be verified with the appropriate Nicopress "Go Gauge".
- Nicopress fittings may only be used with Nicopress tools and "Go Gauges".
Do not mix manufacturers.



Nicopress (Oval Sleeve)
025-250N



Nicopress (Stop Sleeve)
025-250S

Order Information

Number	Description	Weight
Copper Oval Sleeves		
025-125N	1/8" (3 mm), Oval Sleeve, 18-3-M	0.05 lb. (0.02 kg)
025-187N	3/16" (4.76 mm), Oval Sleeve, 18-6-X	0.05 lb. (0.02 kg)
025-250N	1/4" (6 mm), Oval Sleeve, 18-10-F6	0.08 lb. (0.04 kg)
025-312N	5/16" (7.9 mm), Oval Sleeve, 18-13-G9	0.12 lb. (0.05 kg)
025-375N	3/8" (9.5 mm), Oval Sleeve, 18-23-H5	0.15 lb. (0.06 kg)
Copper Stop Sleeves		
025-125S	1/8" (3 mm), Stop Sleeve, 871-18-J	0.01 lb. (0.004 kg)
025-187S	3/16" (4.76 mm), Stop Sleeve, 871-20-M	0.05 lb. (0.02 kg)
025-250S	1/4" (6 mm), Stop Sleeve, 871-23-F6	0.06 lb. (0.03 kg)
025-312S	5/16" (7.9 mm), Stop Sleeve, 871-26-F6	0.06 lb. (0.03 kg)
025-375S	3/8" (9.5 mm), Stop Sleeve, 871-27-F6	0.06 lb. (0.03 kg)
Tools		
025-51MJ	Crimping Tool for 1/8" (3 mm) Oval & Stop, 3/16" (4.76 mm) Stop Sleeves	6 lbs. (2.72 kg)
025-51X850	Crimping Tool for 3/16" (4.76 mm) Oval Sleeves	6 lbs. (2.72 kg)
025-3F6950	Crimping Tool for 1/4" (6 mm) Oval & Stop Sleeves	15 lbs. (6.8 kg)
025-2930*	"Go Gauge" for Nicopress Sleeves & Selected Hand Tools	0.1 lb. (0.05 kg)
*When ordering a gauge specify the tool number on which it will be used.		
*See the web page for swage instructions.		

