STAGETEK® ADA-COMPLIANT RAMP





Our New ADA-Compliant Ramp

Making your event staging accessible for all can be a big undertaking and constructing your own ramp may not be a compliant solution. The StageTek ADA-compliant ramp is not only easy to setup but it meets all current ADA requirements including:

- ✔ Ramp slope
- ✓ Hand rails
- ✓ Landings





Meets the requirements as outlined in the 2015 INTERNATIONAL BUILDING CODE - SECTION 1012

STAGETEK® ADA-COMPLIANT RAMP















Shown with optional mid-rails



PRODUCT SPECIFICATIONS:

- Ramp design meets all guidelines of the Americans with Disabilities Act (ADA) according to the 2015 International Building Code (IBC) - Section 1012.
 - Slope is not steeper than one unit vertical in twelve units horizontal (1:12).
 - Hand rails are continuous throughout ramp.
 - Clear width on ramp is a minimum of 36" (914 mm).
 - Landings are a minimum of 60" x 60" (1524 x 1524 mm) at any direction change.
 - Railings extend 12" (305 mm) at end of handrails.
 - Contrasting color indications designate any elevation changes.

- Multiple ramp configurations available to fit your needs
- Compact storage is ideal for facilities that have limited storage space.
- Parts are labeled for quick set-up.
- Ramp surface comes standard with slip-resistant Quadripple surface. Additional surfaces are available by request.
- Adjustable legs are provided for easy set-up on uneven surfaces.
- Ramp design and brackets allow for attachment to StageTek® or Versalite® stages.
- Ten-year warranty.
- · Optional mid-rails are available.



© 2024 Wenger Corporation USA/7-24/D/W/LT0037F



Minnesota Location

Wenger Phone 800.4WENGER (493-6437) Wenger Worldwide +1.507.455.4100 | Parts & Service 800.887.7145 | wengercorp.com

GearBoss Phone 800.493.6437 | gearboss.com 555 Park Drive, PO Box 448 | Owatonna | MN 55060

New York Location

JR Clancy Phone 800.836.1885 JR Clancy Worldwide +1.315.451.3440 | jrclancy.com | 7041 Interstate Island Road | Syracuse | NY 13209









Brands of Wenger Corporation





