

Transcend® Active Acoustic System

- A system using Transcend Active Acoustic Technology designed for the acoustical enhancement of sound for performance venues
- System includes a series of speakers, microphones, amplifiers, digital signal processing, and a digital audio bus to create different levels of reverberation in performance spaces
- Transcend digital signal processor provides up to four zones of control and that can be expanded by adding additional processors
- Each zone contains 4-channel in, 8-channel out Lexicon active acoustic digital signal processing
- System includes HiQnet communication protocol through Audio Architect for setup, adjustment, and remote monitoring of the system
- Processor includes speech/music detection setting which automatically and gradually reduces the system reverberance when a speech signal is detected over a period of time and increases reverberance when music is detected
- Complete turnkey installation can be provided, including all electrical components, system tuning, wiring/mounting of all speakers, microphones, Transcend, other components and equipment rack; includes system tuning by Wenger
- System requires isolated power transformer and motorized breaker panel, supplied by Wenger, installed by others
- Three-year warranty



System Components

Harman Crown Amplifiers

Networked amplification (Audio Architect)

- DCi 8|300N
 - Channels: 8
 - Sensitivity: 2.0V (34 dB gain)
 - Rated Power Output: 600W per channel into 8/4 ohms
 - Signal to noise ratio: (below rated power 20 Hz to 20 kHz, A-weighted): 108 dB
 - Dimensions: 19" x 3-1/2" x 14-1/4" (483 x 89 x 362 mm)
 - Weight: 23.5 lb (10.66 kg)
- DCi 4|600N (Sub Woofer)
 - Channels: 4
 - Sensitivity: 1.0V (34 dB gain)
 - Rated Power Output: 300W per channel into 8/4 ohms
 - Signal to noise ratio: (below rated power 20 Hz to 20 kHz, A-weighted): 108 dB
 - Dimensions: 19" x 3-1/2" x 14-1/4" (483 x 89 x 362 mm)
 - Weight: 20.1 lb (9.1 kg)
- Other available options: DCi 8|600N, DCi 2|300N, DCi 2|600N, DCi 4|300N, DCi 2|1250N, DCi 4|1250N

Harman JBL Speakers

Wall Mounted Speakers:

- Control 28
 - Frequency Response: (-10 dB) half space wall: 60 Hz to 16 kHz
 - Continuous program power capacity: 175 watts
 - Sensitivity: 92 dB SPL, 1W, 1m
 - Wall mounting brackets included
 - Ball-mount adjustment
 - Dimensions: 11"w x 15"h x 8-1/2"d (279 x 381 x 216 mm)
 - Weight: 12 lb (5.5 kg)
- Control 128 (In-wall)
 - Frequency Response: (-10 dB) half space wall: 30 Hz to 20 kHz
 - Continuous program power capacity: 120 watts
 - Sensitivity: 90 dB SPL, 1W, 1m
 - Designed for mounting in stud walls, optional stud wall frame available
 - Dimensions: 10.1"w x 13.1"h x 4.3"d (257 x 333 x 109 mm), 4" (102 mm) front of wall to back of speaker
 - Weight: 5.5 lb (2.6 kg)

Ceiling Mounted Speakers:

- Control 26
 - Frequency Response: (-10 dB) half space wall: 75 Hz to 20 kHz
 - Continuous program power capacity: 150 watts
 - Sensitivity: 89 dB SPL, 1W, 1m
 - Grill, backcan and tile rails included
 - Dimensions: 10" diameter x 8.3" high (254 x 211 mm) 8-3/4" (222 mm) cut out size
 - Weight: 7.5 lb (3.4 kg)
- Other speakers available: Control 47C, Control 47LP, Control 47HC

Sub Woofer Speakers:

- Surface Mounted Control SB210
 - Frequency Response: (-10 dB) half space wall: 42 Hz to 200 Hz
 - Continuous program power capacity: 800 watts
 - Sensitivity: 95 dB SPL, 1W, 1m
 - Dimensions: 14" x 23.3" x 22.5" (356 x 592 x 572 mm)
 - Weight: 38 lb (17.1 kg)
- Other sub woofers available: Ceiling mounted Control 19CS, Control 312CS

Microphones

- Sennheiser MKHC8040 + MZX 8000
 - Cardioid polar pattern
 - Frequency response: 35 to 20,000 Hz
 - Sensitivity: at 1000 Hz – 20 mV/Pa (-34 dB)
 - Equivalent Noise Ratio Level: 13 dB-A, SPL for 1%
 - Length: 1-5/8" (41 mm), with XLR module – 3" (76 mm), 3/4" (19 mm) dia.
- Other microphones available: Schoeps CCM4 and MK4, Neumann KM100

Harman BSS Digital Signal Processor

- BSS BLU 160
 - Inputs: up to 16 analog with 48V phantom power
 - Outputs: BLUlink digital audio
 - Dimensions: 1U - 1.75"h x 19"w x 12.5"d (44 x 483 x 318 mm)
 - Weight: 9 lb (4.1 kg)

Wenger Transcend Active Acoustic Processor

- System: 48 kHz, 32-bit floating point
- Digital Inputs: 16 microphone, 8 auxiliary
- Digital Outputs: 32 channels of BLU link digital audio
- Maximum number of channels: 256 at 48 kHz
- Latency: 6.3 msec.
- Communication protocol: Harman HiQnet
- Communication Applications: Audio Architect
- Up to four zones of processing
- Dimensions: 3.5"h x 19"w x 8.25"d (89 x 483 x 210 mm)
- Weight: 11.5 lb (5.21 kg)

Harman Control Panels

- AMX Touch Screen Control:
 - 7" diagonal touch screen, wall mounted with custom programmed presets for Transcend System
- BSS Contrio EC-8B
 - Wall mounted ethernet wall controller, HiQnet compatible, 8 programmable buttons
- Also compatible with Crestron control panels

Wenger®

JRCLANCY

GEARBOSS®

© 2024 Wenger Corporation
USA/2024-04

Minnesota Location

Wenger Phone 800.4WENGER (493-6437) Wenger Worldwide +1.507.455.4100 | Parts & Service 800.887.7145 | wengercorp.com
GearBoss Phone 800.493.6437 | gearboss.com
555 Park Drive, PO Box 448 | Owatonna | MN 55060

New York Location

J.R. Clancy Phone 800.836.1885 JR Clancy Worldwide +1.315.451.3440 | jrclancy.com | 7041 Interstate Island Road | Syracuse | NY 13209